

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 February 2003 (13.02.2003)

PCT

(10) International Publication Number
WO 03/013198 A1

(51) International Patent Classification⁷: **H05H 1/24**

Daejeon (KR). UHM, Sae Hoon [KR/KR]; 161-10 Bang i-dong, Songpa-gu, 138-050 Seoul (KR).

(21) International Application Number: PCT/KR02/01407

(22) International Filing Date: 26 July 2002 (26.07.2002)

(74) Agent: YOU, Byung, Sun; 610 Mannyun Officetel, 241 Walpyung-dong, Seo-gu, 302-282 Daejeon (KR).

(25) Filing Language: Korean

(81) Designated States (*national*): AT, AU, BR, CA, CH, CN, DE, DK, ES, GB, ID, IL, IN, JP, MX, NO, NZ, PH, SE, SG, US.

(26) Publication Language: English

(30) Priority Data:
2001-23128 U 30 July 2001 (30.07.2001) KR

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): PLAS-MART CO. LTD [KR/KR]; 2326, School of Natural Science B/D, KAIST, 373-1 Kusong-dong, Yusong-gu, 305-701 Daejeon (KR).


Published:
— with international search report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): LEE, Young Kwan [KR/KR]; 107-102 Sangroksu Apartment, Mannyun-dong, Seo-gu, 302-781 Daejeon (KR). LEE, Sang Won [KR/KR]; 373-1 Guseong-dong, Yuseong-gu, 305-338

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ANTENNA STRUCTURE FOR INDUCTIVELY COUPLED PLASMA GENERATOR



(57) Abstract: An antenna structure for an inductively coupled plasma generator suitable for processing large-diameter wafers or large, flat-panel display devices by making a plasma density distribution uniform and symmetrical with respect to a rotating direction inside a circular or rectangular chamber in which a wafer is processed. In the antenna structure having a powered end to which RF power is applied and a ground end connected to the ground, at least two loop antenna elements are disposed electrically in parallel with each other, the powered ends and ground ends of the respective antennas are disposed symmetrically with respect to the center of the antennas, and the antennas crossing each other such that the powered ends and ground ends thereof are disposed at a part far from a chamber and central parts thereof are disposed at a part close to the chamber.



WO 03/013198 A1